



S·T·A·K

BY  **VELAMP**

**HEAVY DUTY
WORK LIGHTS**

**CATALOGO
2016**





Combo-light

Torcia ricaricabile
Rechargeable flashlight
Torche rechargeable


IS408RST



PACKING	INNER	MASTER
/	pcs	pcs
Blister F5	6	24



1 LED = 1W



6 LED = 3W



MAGNET & HOOK



CODICE/ITEM/CODE	IS408RST
Alimentazione / Power source / Alimentation	230V ~ 50Hz / 6V --- 300mA
Batteria (Capacità/Tipo) / Battery type / Type de batterie	3.7V 1500mA Lithium battery
Autonomia / Runtime / Autonomie	5 ore / hours (6 LED-main body) 7 ore / hours (1 LED-flashlight)
Tecnologia della Luce / Light technology / Technologie de la lumière	6 LED SMD 5730 (main body, 3W) 1 LED SMD 3030 (flash light, 1W)
Lumen / Lumen / Lumen	220 Lm (6LED-main body) 90 Lm (1LED-flashlight)
Durata di vita del LED / LED Life time / Durée de vie de la LED	30000 ore / hours / heures
Tipo di fascio / Kind of beam / Type de faisceau	Luce precisa - Diffusa / Focus beam - Diffuse light : 120°
Portata / Irradiation distance / Portée	18 metri / meters (main body) 40 metri/metres (flashlight)
IP	IP22
Grado di protezione contro gli impatti meccanici statici IK / IK	IK5
Dimensioni prodotto / Product size / Dimensions	19 x 5,9 x 4 cm (normal) 29,5 x 5,9 x 4 cm (pull-out)
Materiale / Material / Matière	ABS and PC
Accessori in dotazione / Accessories / Accessoires fournis	Adattatore 12V / 12V Car adaptor Adaptateur 12V Trasformatore 220V 220V Home adaptor transformateur 220V

Torcia ATEX

Torcia a sicurezza intrinseca per utilizzo in ambienti pericolosi
Intrinsically safe flashlight for use in hazardous locations
Lampe-torche LED à sécurité intrinsèque pour utilisation en milieux dangereux



FATEx01

FATEx01



PACKING	INNER	MASTER
/	pcs	pcs
Blister F5	6	48

	UL USA : UL FILE NO.: 0ERX.E324236 Class I Div 1 & 2 Grp ABCD Class II Div 1 & 2 Grp EFG Class III Temp Code: T4
	IECEX Worldwide : IECEX CERTIFICATE NO.: IECEX UL 11.0042X Ex ia IIC T4 Ga
	Ex Europe : ATEX CERTIFICATE NO.: DEMKO 11 ATEX 1110052X Ⓜ II 1G Ex ia IIC T4
	0539

CODICE/ITEM/CODE	FATEx01
Batteria (Capacità/Tipo) / Battery type / Type de batterie	4 x AA (non fornite)
Autonomia / Runtime / Autonomie	14 ore / hours
Tecnologia della Luce / Light technology / Technologie de la lumière	1W OSRAM HIGH POWER LED
Lumen / Lumen / Lumen	60 Lm
Durata di vita del LED / LED Life time / Durée de vie de la LED	50000 ore / hours / heures
Tipo di fascio / Kind of beam / Type de faisceau	Focus fino a 130m / up to 130 mt
Portata / Irradiation distance / Portée	130 mt
IP	IP67
Dimensioni prodotto / Product size / Dimensions	175 x 45 x 45 mm
Materiale / Material / Matière	ABS



Focus Lens LED Flashlight

ZOOM - LIGHT 100% - LIGHT 30% - STROBE - SOS

STAKTO03

STAKTO01

STAKTO02



STAKTO01



PACKING	INNER	MASTER
	pcs	pcs
Blister F6	6	24

STAKTO02



PACKING	INNER	MASTER
	pcs	pcs
Blister F6	6	24

STAKTO03



PACKING	INNER	MASTER
	pcs	pcs
Blister F6	6	24



TORCE MULTIFUNZIONE CON LENTE FOCALIZZABILE HIGHLUMEN

CODICE/ITEM/CODE	STAKTO01	STAKTO02	STAKTO03
Batteria (Capacità/Tipò) / Battery type / Type de batterie	1 x AA (non in dotazione - not included)	3 x AAA (non in dotazione - not included)	2 x C (non in dotazione - not included)
Autonomia / Runtime / Autonomie	Light 100%: 3 ore / hours Light 30%: 7,5 ore / hours	Light 100%: 4 ore / hours Light 30%: 15 ore / hours	Light 100%: 4 ore / hours Light 30%: 14 ore / hours
Funzioni / Functions / Fonctions	Zoom / Light 100% / Light 30% / SOS	Zoom / Light 100% / Light 30% / Strobe/SOS	Zoom / Light 100% / Light 30% / Strobe/SOS
Tecnologia della Luce / Light technology / Technologie de la lumière	1 LED CREE® XP-E	1 LED CREE® XP-E	1 LED CREE® XP-E
Lumen / Lumen / Lumen	Hi: 80 Lm - Low: 20 Lm	Hi: 180 Lm - Low: 30 Lm	Hi: 210 Lm - Low: 40 Lm
Durata di vita del LED / LED Life time / Durée de vie de la LED	30000 ore / hours / heures	30000 ore / hours / heures	30000 ore / hours / heures
Tipo di fascio / Kind of beam / Type de faisceau	Regolabile / Adjustable: 12°/75°	Regolabile / Adjustable: 12°/75°	Regolabile / Adjustable: 12°/75°
Portata / Irradiation distance / Portée	100 mt	180 mt	200 mt
IP	IPX4	IPX4	IPX4
Dimensioni prodotto / Product size / Dimensions	29ø x 124 mm	36ø x 132 mm	40ø x 172 mm
Materiale / Material / Matière	Alluminio / Aluminium	Alluminio / Aluminium	Alluminio / Aluminium
Accessori in dotazione / Accessories / Accessoires fournis	Clip + Wrist band / Clip + Cinturino	Clip + Wrist band / Clip + Cinturino	Clip + Wrist band / Clip + Cinturino

Robot

Lampada da testa LED CREE®
CREE® LED headlamp
Lampe frontale LED CREE®

CODICE/ITEM/CODE	STH200
Batteria (Capacità/Tipo) / Battery type / Type de batterie	1 x 18650 Lithium (2600Ma) (in dotazione - included)
Autonomia / Runtime / Autonomie	SPOT: 7 ore / hours - FLOOD: 18 ore / hours
Tecnologia della Luce / Light technology / Technologie de la lumière	2 LED - CREE® XP-G2
Lumen / Lumen / Lumen	SPOT: 220 Lm - FLOOD: 110 Lm - SPOT+FLOOD: 350 Lm
Durata di vita del LED / LED Life time / Durée de vie de la LED	30000 ore / hours / heures
Tipo di fascio / Kind of beam / Type de faisceau	SPOT: 30° - FLOOD: 100°
Portata / Irradiation distance / Portée	250 metri / meters
IP	IPX4
Dimensioni prodotto / Product size / Dimensions	89 x 38 x 40,5(3 Bord) mm
Materiale / Material / Matière	PC
Accessori in dotazione / Accessories / Accessoires fournis	AC/DC Adaptor 4 hooks for Hardhat 18650 Battery USB cable

STH200

STH200



PACKING	INNER	MASTER
/	pcs	pcs
Blister F5	6	36





Ve-gun

Faro ricaricabile a LED 3WATT CREE®
Rechargeable 3 W CREE® LED spotlight
Phare rechargeable 3 Watt à LED CREE®



R912

3W
CREE®

R912



8 003910 115446 >

PACKING	INNER	MASTER
/	pcs	pcs
Colour box	-	6



CODICE/ITEM/CODE	R912
Alimentazione / Power source / Alimentation	230-240V ~ 50Hz / 5V --- 200mA
Batteria (Capacità/Tipo) / Battery type / Type de batterie	4 V 2 Ah Piombo ricaricabile / Rechargeable Lead acid battery / Plomb Rechargeable
Tempo di ricarica / Charging time / Temps de charge maxi	12 ore / hours / heures
Autonomia / Runtime / Autonomie	> 16 ore / hours / heures
Tecnologia della Luce / Light technology / Technologie de la lumière	CREE® XPE LED
Potenza in Watt / Watt power / Puissance	3W
Lumen / Lumen / Lumen	220 (luce forte/high beam/forte) - 90 (luce debole/low beam/en position confort)
Durata di vita del LED / LED Life time / Durée de vie de la LED	30000 ore / hours / heures
Tipo di fascio / Kind of beam / Type de faisceau	focus
Portata / Irradiation distance / Portée	300 m
Dimensioni prodotto / Product size / Dimensions	170 x 86 x 177 mm
Materiale / Material / Matière	ABS
IP	44
Accessori in dotazione / Accessories / Accessoires fournis	Adattatore 12V / 12V Car adaptor / Adaptateur 12V Trasformatore 220V / 220V Home adaptor / transformateur 220V



**10W
CREE®**



NEW!
with ANTI
BLACK-OUT
function



DOOMSTER PRO MASTER

Faro ricaricabile a LED XML CREE®
Rechargeable XML CREE® LED spotlight
Phare rechargeable LED XML CREE®



PACKING ☑ / ☑ Suitcase with handle	INNER ☑ pcs 2	MASTER ☑ pcs 6
--	---------------------	----------------------

CODICE/ITEM/CODE	ST999-10W
Alimentazione / Power source / Alimentation	220V ~ 50Hz / 5V --- 200mA
Batteria (Capacità/Tipo) / Battery type / Type de batterie	Pb 4V 4000mAh
Tempo di ricarica / Charging time / Temps de charge maxi	15 ore / hours
Autonomia / Runtime / Autonomie	Hi: 4 ore / hours - Low: 15 ore / hours - COB: 7,5 ore / hours
Tecnologia della Luce / Light technology / Technologie de la lumière	CREE® XML LED
Potenza in Watt / Watt power / Puissance	10W
Lumen / Lumen / Lumen	735 Lm
Durata di vita del LED / LED Life time / Durée de vie de la LED	30000 ore / hours / heures
Tipo di fascio / Kind of beam / Type de faisceau	focus
Portata / Irradiation distance / Portée	1000 m
Dimensioni prodotto / Product size / Dimensions	208 x 144 x 162 mm
Materiale / Material / Matière	ABS/NYLON
IP	IP44
Accessori in dotazione / Accessories / Accessoires fournis	Tracolla / Carry strap Adattatore 12V / 12V Car adaptor Trasformatore 220V / 220V Home adaptor



NEW!
20W
CREE

R920

Trainspotting

Faro ricaricabile a LED 20 WATT CREE®
Rechargeable 20 W CREE® LED spotlight
Phare rechargeable 20 Watt à LED CREE

R920

R920



8 003910 902152 >

POWER BANK FUNCTION







TRIPOD ADAPTOR



RED REAR LIGHT



NEW!
with **ANTI BLACK-OUT**
function

PACKING	INNER	MASTER
 / 	 pcs	 pcs
Colour box	-	6



CODICE/ITEM/CODE	R920
Alimentazione / Power source / Alimentation	220V ~ 50Hz / 7,5V --- 350mA
Batteria (Capacità/Tipo) / Battery type / Type de batterie	6 V 4 Ah Piombo ricaricabile / Rechargeable Lead acid battery / Plomb Rechargeable
Tempo di ricarica / Charging time / Temps de charge maxi	14 ore / hours / heures
Autonomia / Runtime / Autonomie	3 ore / hours / heures (luce forte/high beam/forte) 8 ore / hours / heures (luce debole/low beam/en position confort)
Tecnologia della Luce / Light technology / Technologie de la lumière	LED CREE® XHP 50
Potenza in Watt / Watt power / Puissance	20W
Lumen / Lumen / Lumen	1600
Durata di vita del LED / LED Life time / Durée de vie de la LED	30000 ore / hours / heures
Tipo di fascio / Kind of beam / Type de faisceau	focus
Portata / Irradiation distance / Portée	> 1500 m
Dimensioni prodotto / Product size / Dimensions	205 x 175 x 185 mm
Materiale / Material / Matière	ABS/PP
IP	IP43
Accessori in dotazione / Accessories / Accessoires fournis	Tracolla / Carry strap Adattatore 12V / 12V Car adaptor Adattatore per trepiede / Tripod adaptor Trasformatore 220V / 220V Home adaptor Uscita USB per ricarica dispositivi compatibili / USB output for powerbank function

**3800
LUMEN**



IP54



IR50RST



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	1	4



IR50RST

Faro ricaricabile a LED 50W con altoparlante Bluetooth

50W LED Rechargeable floodlight with Bluetooth speaker

Projecteur rechargeable LED 50W avec haut-parleur Bluetooth

CODICE/ITEM/CODE	IR50RST
Alimentazione / Power source / Alimentation	220V ~ 50Hz / 12V === 2,3A
Batteria (Capacità/Tipò) / Battery type / Type de batterie	Li-ion 7,4V 13,2Ah
Tempo di ricarica / Charging time / Temps de charge maxi	5 ore / hours
Autonomia / Runtime / Autonomie	Hi: 6 ore / hours - Low: 15 ore / hours
Tecnologia della Luce / Light technology / Technologie de la lumière	COB LED
Potenza in Watt / Watt power / Puissance	50W
Lumen / Lumen / Lumen	3800 Lm
Tipo di luce / Kelvin degrees	6500K
Durata di vita del LED / LED Life time / Durée de vie de la LED	30000 ore / hours
Tipo di fascio / Kind of beam / Type de faisceau	Diffuso / Diffuse 105°
Dimensioni prodotto / Product size / Dimensions	260 x 110 x 275 mm
Materiale / Material / Matière	AL+PC
IP	IP54
Accessori in dotazione / Accessories / Accessoires fournis	Adattatore 12V / 12V Car adaptor Trasformatore 220V / 220V Home adaptor Uscita USB per ricarica dispositivi compatibili / USB output for powerbank function

IS180W

Luce da lavoro LED 80W con altoparlante Bluetooth


80W LED Worklight with Bluetooth speaker

Projecteur de chantier LED 80W avec haut-parleur Bluetooth

CODICE/ITEM/CODE	IS180W
Alimentazione / Power source / Alimentation	220V ~ 50Hz
Tecnologia della Luce / Light technology / Technologie de la lumière	COB LED
Potenza in Watt / Watt power / Puissance	80W
Lumen / Lumen / Lumen	5500 Lm
Tipo di luce / Kelvin degrees	6500K
PPortata / Irradiation distance / Portée	10 mt
Durata di vita del LED / LED Life time / Durée de vie de la LED	30000 ore / hours
Tipo di fascio / Kind of beam / Type de faisceau	Diffuso / Diffuse 105°
Dimensioni prodotto / Product size / Dimensions	344 x 116 x 312 mm
Materiale / Material / Matière	AL+PC
IP	IP54
Cavo / Cable	H07RN-F 3G1.5mm ² Lungo 5 mt / Length: 5 mt
Accessori in dotazione / Accessories / Accessoires fournis	1 presa shuko max 3000W / 1 shuko socket max 3000W

IP54

5 mt
CAVO: H07RN-F
3 x 1,5 mm



5500 LUMEN

IS180W



PACKING	INNER	MASTER
/	pcs	pcs
Colour box	1	4



S·T·A·K

BY  **VELAMP**

 **VELAMP**

Comunque luce

VELAMP INDUSTRIES SRL - Via Lavoratori Autobianchi PTB Lotto 8 - 20832 Desio (MB) Italy

Tel. +39 0362 306797 - Fax +39 0362 620480 - info@velamp.com - www.velamp.com

Velamp Industries France SARL SIRET : 7888 10869 00016 APE : 4791B - 6, Rue Edouard Nignon BP 37201 - 44372 Nantes CEDEX 3

Tel. +33 6 08 97 88 87 • fpresta@velamp.com

Edizione 02/2016

